

UTS 15 TECHNICAL SPECIFICATIONS

- Pump-action 12-gauge shotgun chambered for 2 ½", 2 ¾" & 3" magnum ammunition.
- Dual 7-round magazines with automatic alternating or selectable feed, snap open loading ports and cartridge counter magazine followers*
- Integrated top mounted picatinny rail for iron sights or optics.
- Windage adjustable rear sight with flip up large aperture peep or big game V. Elevation adjustable front sight.*
- Technical polymer receiver with integrated spring loaded shell feeding device and quick removable fire control housing containing the hammer, sear and disconnect.
- Spring assisted pin ejector.
- Fiber reinforced flip up stock / shell funnel.
- Fiber reinforced butt plate with 1", 8 durometer (A scale) energy absorbing recoil pad.
- 4140 steel bolt body, precision machined and heat treated 4140 steel rotary bolt heat with three locking lugs.
- Precision machined and heat treated 4140 barrel extension with three locking lug mortises.*
- Precision machined 4140 steel barrel with muzzle threaded to accept Beretta style chokes.
- Precision machined 4140 steel flash suppressor with strike bezel and full length knurling.*
- Internally mounted point-and-shoot high intensity lens focused LED spotlight and full adjustable laser sight, push button operated.*
- Forward, rear and mid-point quick detachable sling swivel mounting points. Mil Spec quick detachable swivels.*
- Matt black non-glare textured finish on all polymer parts.
- Matt black chrome or black oxide on all steel parts.
- Matt black non-glare anodizing on all aluminum parts.
- Overall length 28.3".
- Weight 6.9 lbs.
- No tools required field stripping in 45 seconds.

**Sights, breeching choke, laser / spotlight are not included on the Standard UTS-15; available as an accessory for an additional charge.*